

# Canon

Delighting You Always



## PROFESSIONAL CAMCORDER

Jadikan *camcorder* profesional Canon sebagai mitra dalam setiap perekaman. Beragam fitur dan sistem yang tangguh dari Canon akan memudahkan Anda dalam menghasilkan rekaman berkualitas tinggi.

### CANON Pro DV Camera



#### XC10

- Sensor: 1.0-inch 4K-compatible high-sensitivity CMOS
- 4K video recording 30 p H.264 Intra Frame 4:2:2/8 bit
- Full HD 60p H.264 LongGOP 4:2:2/8 bit
- Image processing platform DIGIC DV5
- Canon Log for Wide DR Gamma
- 10x optical zoom 4K video lens
- 2 Card slot CFast 2.0 & SD Card

Ref. No. XC10



#### XA10/XA30/XA35

- Sensor: 1/3-inch (XA10); Sensor: 1/2.84-inch (XA30/XA35)
- AVCHD (PAL) FHD 1920 x 1080/1440 x 1080 (AC-3/H.264 standard)
- MP4 (PAL) FHD, HD, SD 1920 x 1080/1280 x 720/640 x 360 (AAC/H.264 standard)
- Optical Zoom: 10X (XA10), 20X (XA30/XA35)
- Image Stabilization
- LCD Panel 3.5-inch, Widescreen OLED screen (XA30/XA35)
- GenLock or TimeCode, HD/SD-SDI terminal (XA35)
- Built-in Memory 64 GB (XA10)
- 2x Slot SD Card (Relay Recording, Dual Recording Supported)
- Built-in Wi-Fi (XA30/XA35)

Ref. No. XA-10/XA-30/XA-35



#### XF300/XF305

- 3 Canon Native 1920 x 1080 CMOS Image Sensors 1/3 inch
- Multiple Recording Bit Rates, Resolutions and Variable Frame Rates
- MPEG-2 4:2:2 50 Mbps Codec (Canon XF Codec)
- Major NLE Software Compatibility
- Large HD LCD, 4.0 inch 35° of forward movement
- Genuine Canon 18x HD L-series Lens Optical Zoom, 29.3-527.4 mm
- Custom Picture, Slow & Fast Motion, Interval Shooting, Waveform, Vectorscope
- HD-SDI (XF305), 3G-SDI (XF305), Time Code, Genlock

Ref. No. XF300/XF305



#### XF200/XF205

- 1920 x 1080, 1/2.84" CMOS Sensor
- 20x Zoom with Zoom, Focus, Iris Rings
- 50 Mbps MPEG-3 & 35 Mbps Mp4 Recording
- 4:2:2 Color Sampling
- 23.98/29.97p, 59.94i/p
- Dual CF & Single SDXC Card Slots
- Dual XLR Inputs, 4-Channels of Audio
- Orientable Hand Grip
- HDMI, Wi-Fi & Ethernet
- HD-SDI (XF205), 3G-SDI (XF205), Time Code, Genlock

Ref. No. XF200/XF205



#### XF100/XF105

- Sensor HD CMOS Pro 1/3 inch, 2.4 megapixels
- Multiple Recording Bit Rates, Resolutions and Variable Frame Rates
- MPEG-2 4:2:2 50 Mbps Codec (Canon XF Codec)
- Infrared Shooting, waveform, Vectorscope and Custom Picture
- 2 slot CF Memory Card Recording
- Genuine Canon 10x HD Video Lens
- 3.5 inch, 920k dot LCD Monitor
- GenLock or TimeCode, HD/SD-SDI terminal (XF105)

Ref. No. XF100/XF105