

## NETWORK CAMERA



### MEGAPIXEL Series



#### VB-M42/M-42B

- 60.4° wide angle-of-view
- 1.3 M high pixels
- Min. illumination: Color 0.6 lux/BW 0.06 lux
- 20x optical zoom
- PTZ Function
- Intelligent functions installed
- H.264 supported
- ONVIF supported

Ref. No. VB-M42



#### VB-M620D/M620VE

- 111° wide angle-of-view
- 1.3 M high pixels
- Min. illumination: Color 0.4 lux/BW 0.04 lux
- PTRZ function for installation
- 3x optical zoom
- Intelligent functions installed
- H.264 supported
- Vandal Dome ip66 (M600VE Only)

Ref. No. VB-M620D / M620VE



#### VB-M720F

- 112° wide angle-of-view
- 1.3 M high pixels
- Min. illumination: Color 0.4 lux/BW 0.04 lux
- PTRZ function for installation
- 3x fixed box
- Intelligent functions installed
- H.264 supported

Ref. No. VB-M720F

### FULL HD Series



#### VB-H43/H43B

- 60,4-degree wide angle-of-view
- 2.1 M high pixels (1920 x 1080)
- Min illumination: Color 0.4 lux/BW 0.02 lux
- 20x optical zoom
- PTZ Function
- Intelligent functions installed
- H.264 supported
- ONVIF supported

Ref. No. VB-H43/H43B



#### VB-H630D/H630VE

- 112-degree wide angle-of-view
- 2.1 M high pixels (1920 x 1080)
- Min illumination: Color 0.3 lux/BW 0.015 lux
- PTRZ function for installation
- 3x optical zoom/4x digital zoom
- Intelligent functions installed
- H.264 supported
- Vandal Dome ip66 (H610VE Only)

Ref. No. VB-H630D / H630VE



#### VB-H730F

- 112-degree wide angle-of-view
- 2.1 M high pixels (1920 x 1080)
- Min illumination: Color 0.3 lux/BW 0.015 lux
- PTRZ function for installation
- 3x optical zoom/4x digital zoom
- Intelligent functions installed
- H.264 supported

Ref. No. VB-H730F

### COMPACT FULL HD Series



#### VB-S900F

- 96-degree wide angle-of-view
- 2.1 M high pixels (1920 x 1080)
- Min. illumination: color 0.4 lx/BW 0.2 lx
- Digital PTZ function
- 4x digital zoom
- Intelligent functions installed
- H.264 supported
- ONVIF supported

Ref. No. VB-S900F



#### VB-S800D

- 95-degree wide angle-of-view
- 2.1 M high pixels (1920 x 1080)
- Min. illumination: color 0.45 lx/BW 0.25 lx
- Digital PTZ function
- 4x digital zoom
- Intelligent functions installed
- H.264 supported
- ONVIF supported

Ref. No. VB-S800D



#### VB-S31D

- 95-degree wide angle-of-view
- 2.1 M high pixels (1920 x 1080)
- Min. illumination: color 0.45 lx/BW 0.25 lx
- Pan & tilt function
- 4x digital zoom
- Intelligent functions installed
- H.264 supported
- ONVIF supported

Ref. No. VB-S31D



#### VB-S30D

- 77.7-degree wide angle-of-view
- 2.1 M high pixels (1920 x 1080)
- Min. illumination: color 0.95 lx/BW 0.5 lx
- 3.5x optical zoom/4 x digital zoom
- PTZ function
- Intelligent functions installed
- H.264 supported
- ONVIF supported

Ref. No. VB-S30D